


Modules for RELPOL DIN-Rail sockets GZ92, GZ80, GZ96, GZWR2, GZW4



| Description | Voltage | Circuit | LED color | Type |
|---|-----------------|---------|-----------|-------|
| Module with diode | 6/230 VDC | | | 12 |
| Protection against polarity inversion | 6/230 VDC | | | 22 |
| Module with diode and LED | 6/24 VDC | | Red | 32 |
| Protection against polarity inversion | 24/60 VDC | | Green | 32 V |
| Coil energizing indication | 110/230 VDC | | Red | 32 B |
| | | | Green | 32 BV |
| Module with diode and LED | 6/24 VDC | | Red | 32 C |
| | 24/60 VDC | | Green | 32 CV |
| | 110/230 VDC | | Green | |
| Protection against polarity inversion | 6/24 VDC | | Red | 42 |
| | 24/60 VDC | | Green | 42 V |
| | 110/230 VDC | | Red | 42 B |
| Coil energizing indication | | | Green | 42 BV |
| | | | Red | 42 C |
| | | | Green | 42 CV |
| Module with RC group | 6/24 VAC | | | 52 B |
| | 24/60 VAC | | | 52 D |
| | 110/240 VAC | | | 52 C |
| Arc distinguish circuit | | | | |
| | | | | |
| | | | | |
| Module with LED | 6/24 V AC/DC | | Red | 62 |
| | 24/60 V AC/DC | | Green | 62 V |
| | 110/230 V AC/DC | | Red | 62 E |
| No protection against polarity inversion | | | Green | 62 EV |
| | | | Red | 92 |
| | | | Green | 92 V |
| Coil energizing indication. AC/DC voltage allowed | | | | |
| | | | | |
| | | | | |
| Module with LED and varistor | 6/24 V AC/DC | | Red | 62 C |
| | 24/60 V AC/DC | | Green | 62 CV |
| | 110/230 V AC/DC | | Red | 62 D |
| No protection against polarity inversion | | | Green | 62 DV |
| | | | Red | 92 C |
| | | | Green | 92 CV |
| Coil energizing indication AC/DC voltage allowed | | | | |
| | | | | |
| | | | | |
| Module with varistor group | 24 VAC | | | 72 |
| | 130 VAC | | | 72 A |
| | 230 VAC | | | 82 |
| No indication | | | | |
| | | | | |
| Protection against overvoltage | | | | |
| | | | | |
| Module with resistor | 110/230 VAC | | | 102 |