

- ▶ DIN-Rail mounting
- ▶ Width 17.5mm
- ▶ Without zero reset
- ▶ Without terminal cover



▶ Technical data

▶ 1. Indicators

Counter capacity:	99 999h
Accuracy of reading:	0.1h
Numeral colour:	white, decimal figures red
Numeral height:	2.6mm
Operation indicator:	flashing LED

▶ 2. Mechanical design

Self-extinguishing plastic housing, IP rating IP50	
Class of protection III (up to 48V DC)	
Mounted on DIN-Rail TS 35 according to EN 50022	
Shockproof terminal connection according to VBG 4, IP rating IP20	
Initial torque:	max. 4Nm
Terminal capacity:	
1 x 1.5 to 10mm ² without multicore cable end	
2 x 0.8 to 2,5mm ² without multicore cable end	
1 x 1.0 to 6mm ² flexible with multicore cable end	
2 x 0.8 to 2,5mm ² flexible with multicore cable end	

▶ 3. Input circuit

Supply voltage:	12 to 48V DC
Tolerance:	±10%
Rated consumption:	12V DC approx. 20mW

▶ 4. Ambient conditions

Ambient temperature:	-10 to +50°C
Storage temperature:	-10 to +50°C
Transport temperature:	-10 to +50°C
Relative humidity:	<90%

► Dimensions

